

Lighten up with  
**DairyFlow II**

*Lightweight, high-performance  
milk tubing*



Up to  
**25% lighter**  
than other  
co-extruded tubing.

New DairyFlow II tubing by Conewango was specifically designed to meet the demands of milkers on progressive, high-performing dairy operations. We made it lighter – **up to 25% lighter than other co-extruded tubing** – to allow the milking machine to hang on the udder with less slip. We made it **more flexible** than other co-extruded tubing for better unit alignment, more even milkouts and flexibility even in sub-freezing temperatures. We made it **more durable**, with a smooth, sanitary, easy-to-clean inner surface that resists CIP acid detergents, and an advanced polymer exterior that resists tears and abrasions.

We also made DairyFlow II **easier on the environment**, with a plasticizer-free, animal ingredient-free material with no harmful phthalates or carbon, assuring producers of maximum milk purity and quality.



No dairy tubing delivers all these benefits at a lighter weight! For more information about new DairyFlow II, contact your Conewango dealer representative today.

**800.828.9258**  
**Conewango.com**

### Sizing

Part Number	ID	OD	Wall	Length
5/8 – 100 DFII	5/8"	1-1/16"	7/32"	100'
3/4 – 100 DFII	3/4"	1-3/16"	7/32"	100'

**Conewango**  
Serving the Dairyman since 1931

©2015 Conewango